

VHX (objem 24 až 3000 l) tlakové nádoby

- vyrobené z nerezové oceli AISI316L
- z vnější i vnitřní strany mořené a pasivované
- vyrobené dle směrnice PED 68/2014ES
- pro stlačený vzduch a dusík
- pracovní tlak 11/12 bar
- pracovní teplota -80/+120 °C (pro objem od 500 litrů -55/+80 °C)



Obj. č.	Objem (l)	Tlak (bar)	Rozměry (mm)			Hmotnost (kg)
			De	A	H1	
VHX5-11	5	11	150	314	50	6
VHX10-12	10	12	169	506	85,5	8
VHX15-12	15	12	196	624	80	11
VHX24-11	24	11	240	634	90	13
VHX50-11	50	11	305	784	47,5	21
VHX100-11	100	11	370	966	71	32
VHX150-11	150	11	446	1 064	65	49
VHX200-11	200	11	446	1 364	65	55
VHX270-11	270	11	500	1 558	65	69
VHX500-11	500	11	600	1 864	96	125
VHX1000-11	1 000	11	800	2 144	100	377

Připojení

Obj. č.	x	y	k	j	z
VHX5-11	1/2"	-	-	-	1/2"
VHX10-12	1/2"	-	1/2"	-	1/2"
VHX15-12	1/2"	-	1/2"	-	1/2"
VHX24-11	1/2"	-	1/2"	-	1/2"
VHX50-11	1/2"	3/8"	3/8"	-	1/2"
VHX100-11	1/2"	3/8"	1/2"	3/8"	3/8"
VHX150-11	1/2"	3/8"	1/2"	3/8"	1/2"
VHX200-11	1/2"	3/8"	1/2"	1/2"	3/8"
VHX270-11	1/2"	3/8"	1"	1/2"	1/2"
VHX500-11	1/2"	3/8"	1"	1/2"	1/2"
VHX1000-11	2"	3/4"	1"	1/2"	1/2"

